CLAIMS

1. A multiple-original-output ("Mopying") control system for use with a Mopy-enabled multifunction device (MFD), the system comprising:

a source-selection determiner configured to determine a source selected for a Mopy in a Mopy job, wherein the source for the Mopy may be selected from multiple sources on the MFD;

a destination-selection determiner configured to determine a destination selected for a Mopy in a Mopy job wherein the destination for the Mopy may be selected from multiple destinations on the MFD;

a Mopy-job formatter configured to format a Mopy job that includes source-selecting directions for at least one Mopy in the job and destination-selecting directions for at least one Mopy in the job;

a Mopy-job transmitter configured to transmit the Mopy job to a MFD.

2. A MFD comprising:

a printing engine;

multiple sources;

multiple destinations;

a receiver configured to receive a Mopy job from a Mopying control system as recited in claim 1.

3. A printer driver comprising a Mopying control system as recited in claim 1.

4. An application comprising a Mopying control system as recited in claim 1.

5. An operating system comprising a Mopying control system as recited in claim 1.

6. A method facilitating multiple-original-output ("Mopying") control of a Mopy-enabled multifunction device (MFD), the method comprising:

specifying a source for a Mopy in a Mopy job, wherein the source for the Mopy may be one of multiple sources on the MFD;

specifying a destination for a Mopy in a Mopy job wherein the destination for the Mopy may be one of multiple destinations on the MFD.

7. A method as recited in claim 6, further comprising:

formatting a Mopy job, such job includes source-selecting directions for at least one Mopy in the job and destination-selecting directions for at least one Mopy in the job;

transmitting the Mopy job to a MFD.

8. A computer-readable medium having computer-executable instructions that, when executed by a computer, performs the method as recited in claim 6.

9. A multiple-original-output ("Mopying") control system for use with a Mopy-enabled multifunction device (MFD), the system comprising:

a source-selection specifier configured to select a source for each Mopy in a Mopy job, wherein a source for the Mopy may be selected from multiple sources on the MFD;

a destination-selection specifier configured to select a destination for each Mopy in a Mopy job, wherein a destination for the Mopy may be selected from multiple destination on the MFD.

10. A system as recited claim 9, further comprising:

a Mopy-job formatter configured to format a Mopy job that includes source-selecting directions for each Mopy in the job and destination-selecting directions for each Mopy in the job;

a Mopy-job transmitter configured to transmit the Mopy job to a MFD.

11. A MFD comprising:

a printing engine;

multiple sources;

multiple destinations;

a receiver configured to receive a Mopy job from a Mopying control system as recited in claim 9.

12. A printer driver comprising a Mopying control system as recited in claim 9.

13. An application comprising a Mopying control system as recited in claim 9

14. An operating system comprising a Mopying control system as recited in claim 9.